


SPECIFICATION

ITEM		MODEL		XZU720_{LA}	XZU730_{LA}
ENGINE	MODEL	N04C-VB			
	TYPE	Diesel, 4-cy.,vertical, 4-cyl. in-line, overhead valve, water cooled, direct injection			
	DISPLACEMENT	cc	4,009		
	MAX OUTPUT (JIS GROSS)	kW(PS)/rpm	114 (156) / 2,800		
	MAX. TORQUE (JIS GROSS)	Nm(kgfm)/rpm	429 (43.8) / 1,400		
	BORE & STROKE	mm	104 x 118		
	FUEL INJECTION SYSTEM		Electronic control Commonrail type		
	AIR INTAKE SYSTEM		Turbo-intercooled, stack type		
TRANSMISSION	MODEL/NO. OF SPEED	A860E / Automatic 6-Speed			
	TYPE	Six (6) forward and one (1) reverse, overdrive			
	RATIO (1st - Top)	3.742 / 0.634			
AXLE	FRONT TYPE	Reversed Elliot, "I" section beam			
	CAPACITY	kg	3,100		
	REAR TYPE	Full floating, single reduction, single speed by hypoid gearing			
BRAKE	CAPACITY	kg	5,100		
	SERVICE BRAKE TYPE	Hydraulic system with two leading shoes for front wheels and dual two leading shoes for rear wheels with auto brake shoe adjuster			
	SERVICE BRAKE CONTROL	Vacuum servo hydraulic, dual circuits with Antilock Braking System (ABS) and power assist			
SUSPENSION	PARKING BRAKE TYPE	Mechanical, internal expanding, acting on transmission output shaft			
	EXHAUST BRAKE TYPE	Electric-vacuum actuator with valve in exhaust pipe			
	FRONT TYPE	Semi elliptic leaf spring with dual acting shock absorber and stabilizer			
FRAME	REAR TYPE	Semi elliptic main and auxiliary leaf spring with dual acting shock absorber			
	FRAME WIDTH	mm	750		
CABIN	HEIGHT x WIDTH x THICKNESS	mm	192.8 x 65 x 5.9		
	TILTING	Mechanical Type			
	STEERING	Telescopic & tilt steering column with locking device, recirculating ball with hydraulic booster, integral type			
	POWER WINDOW	Equipped			
WHEELS & TIRES	CENTRAL LOCKING	Equipped			
	SEAT BELT	Equipped			
	WHEEL TYPE	6 Stud			
ELECTRICAL	RIM SIZE	17.5 x 6.00GS - 127			
	TIRE SIZE	215/75 R 17.5 - 12PR			
	TYPE	24V, Negative Earth			
FUEL TANK CAPACITY	BATTERIES	12V x 2 , Series connection			
	ALTERNATOR CAPACITY	24V - 60 Amps			
PERFORMANCE		L	100		
G.V.W Rating		kg	5,000		
PERFORMANCE	MAX SPEED	km/h	100 (* With Speed Limiter)		
	GRADEABILITY	(tan Ø) %	60		
TRANSMISSION RATIO	MODEL	A860E			
	1st	3.742			
	2nd	2.003			
	3rd	1.343			
	4th	1.000			
	5th	0.773			
	6th	0.634			
REAR AXLE	REVERSE	3.697			
	MODEL	SH12			
	RATIO	5.125			
DIMENSION & MASS					
CHASSIS MASS (with std tools set & spare tire)	FRONT AXLE	kg	1,645	1,665	
	REAR AXLE	kg	920	935	
	TOTAL	kg	2,565	2,600	
DIMENSION	WHEELBASE	WB	mm	3,870	4,200
	OVERALL LENGTH	OL	mm	6,740	7,250
	OVERALL WIDTH	OW	mm		1,995
	OVERALL HEIGHT	OH	mm		2,225
	CAB TO AXLE CENTER	CA	mm	3,310	3,640
	FRONT OVERHANG	FOH	mm		1,115
	REAR OVERHANG	ROH	mm	1,755	1,935
	FRONT TREAD	FT	mm		1,655
	REAR TREAD	RT	mm		1,520
	TURNING RADIUS (on tire)		mm	6,400	6,900
	SEATING CAPACITY		3		

HINO MOTORS SALES (MALAYSIA) SDN. BHD. is engaged in an ongoing research and development program, and reserves the right to change specification without prior notice in order to pass on to the customer any resulting advances or technical refinements. All specifications of the product are within normal manufacturing allowances and tolerances.



HINO Authorized Dealer:

Ver. 01/1.2017



HINO 300 SERIES

Compliance with United Nations Regulation (UNR) by JPJ



XZU720_{AUTO} 156ps

XZU730_{AUTO} 156ps

Designed GVW 5,000 kg (6 Wheeler)

WARRANTY*
36 MONTHS
or 100,000KM

FREE*
SERVICE PROGRAM
3 TIMES
(1st-3rd Service)

FREE*
PARTS PROGRAM
7 TIMES
(4th-10th Service)

BREAKDOWN
24 HOURS SERVICE
Toll Free: 1800-88-3666


Terms and Conditions apply*

HINO MOTORS SALES (MALAYSIA) SDN BHD (187863-U)

Selangor: Lot PT 24, Jalan 223, Section 51A, 46100 Petaling Jaya, Selangor Darul Ehsan, Malaysia. Tel: (603) 7957 5199 (12 lines) Fax: (603) 7954 3276
Sarawak: Lot 1076, Block 218, 4th Mile, Penrissen Road, 93250 Kuching, Sarawak, Malaysia. Tel: (082) 451 611 (5 lines) Fax: (082) 451 993
Sabah: Miles 4 1/2 Jalan Tuaran, Lot No. 353, Taman Cempaka, Likas, 88450 Kota Kinabalu, Sabah, Malaysia. Tel: (088) 393 663 Fax: (088) 424 223



www.hino.com.my

PERFORMANCE



EURO 3
XZU720 AUTO
XZU730 AUTO

Model:
N04C-VB
 Type:
**4,009cc 4-cylinder in-line
 Electronic Control
 Commonrail**
 Output (kW/rpm):
114 (156PS)/2,800rpm
 Torque (Nm/rpm):
429Nm (43.8kgfm)/1,400rpm



Frame


The frame is both very strong and lightweight



Suspension

The leaf spring suspension offers high durability and flexibility for stability on rough roads.

COMFORTABILITY



Seat Slide

The seat rails are set on an incline to accommodate your seating position.



Folding Type Automatic Transmission

The shift lever and side lever fold down, making it easy to move around the driver compartment.



LED Meter Panel

The meter cluster features highly visible readouts of necessary vehicle information.



Overhead Console

Greater convenience for documents storage with open section which allows easy access.



Wide Free Rack


Ergonomically designed open storage space and within driver's reach for greater convenience.



Work Space

Intuitively designed, spacious and comfortable, the cab space allows drivers to perform at their best.

SAFETY



Antilock Braking System (ABS)

ABS helps the driver maintain control of the vehicle when braking on a slippery surface by selectively controlling the braking force of individual wheel in order to prevent the wheels from locking.



EGIS Cab (Emergency Guard Impact Safety)

The EGIS Cab Design is one of HINO'S passive safety features, enhancing the rigidity of the cab.



Drum Brake

Equipped with auto brake shoe adjuster to ensure safe & effective braking. It features easy maintenance without compromising on performance.



Tubeless Tyres

Provides good tyre puncture resistance for better safety. Better fuel efficiency due to lighter tyre and lower rolling resistance.



Stabilizer

The stabilizer have been lengthened and feature a link bracket, maintaining high effectiveness and stability.



Door Impact Beams

The side impact beams built into the doors of 300 Series increase the level of protection for driver and passenger in the event of a collision from the side.




Side Mirror

The door-mounted outer mirrors enhance driver's vision. It features partitioned mirror surfaces encased in an aerodynamic and low-profile shell.



Wide View Pillars

The front pillars are designed to be as narrow as possible to ensure a nearly uninterrupted view, allowing the driver to easily see pedestrians and cyclist, without any compromise in structural integrity.



Energy-Absorbing Steering Wheel and Column


The energy-absorbing steering wheel and column reduce collision force.



Headlamp Leveling Switch

The Headlamp Leveling Switch can be used to adjust the headlamp illumination distance.

APPLICATION



Model	XZU720 (Auto)	XZU730 (Auto)
Standard	16.9	18.5


● Drive Axle

Body Type


A truck for every application of bodies suit your type of business.




General Cargo




Box




Curtain Sider



Refrigerated



Tipper




Crane Cargo



Roll On Roll off



Tanker



Garbage Compactor

Note : Some images may be used for illustration purposes only.